



VARI TARGET WHITE CAP

Variable Flow Nozzle with Extremely Coarse Droplet

Features

- Flow rate variable from 0.2 to 1.5 gpm
- Compact size to prevent tip damage
- Produces Extremely Coarse droplets
- Offers low percentage of driftable droplets
- Provides uniform spray coverage at low pressure and low speed



VT110XC
VariTarget White Cap

Application Chart

Nozzle Pressure PSI	Nozzle Flow Rate GPM	Droplet size	20" Nozzle Spacing						
			US Gallons / Acre - Based on Water						
			4 MPH	6 MPH	8 MPH	10 MPH	12 MPH	15 MPH	20 MPH
15	0.20	XC	14.9	9.9	7.4	5.9	5.0	4.0	3.0
20	0.25	XC	18.6	12.4	9.3	7.4	6.2	5.0	3.7
25	0.30	XC	22.3	14.9	11.1	8.9	7.4	5.9	4.5
30	0.40	XC	29.7	19.8	14.9	11.9	9.9	7.9	5.9
38	0.60	XC	44.6	29.7	22.3	17.8	14.9	11.9	8.9
41	0.80	XC	59.4	39.6	29.7	23.8	19.8	15.8	11.9
44	1.00	VC	74.3	49.5	37.1	29.7	24.8	19.8	14.9
47	1.15	VC	85.4	56.9	42.7	34.2	28.5	22.8	17.1
55	1.35	VC	100.2	66.8	50.1	40.1	33.4	26.7	20.0
60	1.50	VC	111.4	74.3	55.7	44.6	37.1	29.7	22.3

Optimum Spray Height

Spacing	Spray Height
20"	20"